

WebeyeCMS

Innovation House, Kestral Road, NG18 5FT Sales@webeyecms.com
0115 714 9990





Wireless HD 4G PIR Camera

OCULI HD is a battery powered, standalone wireless PIR detector with a built-in 5 megapixel camera. It provides rapid visual verification of captured events using the 4G mobile network. Units and sites can be self-monitored and controlled via the webeyeCMS portal and mobile phone app. OCULI HD can be used anywhere with a good 4G signal. We can supply non-steered M2M,4G SIMs on both single network and multi network. OCULI HD will support two way calls. All footage is stored on our cloud servers so it can be easily downloaded for prosecution purposes.




A solar kit is available which facilitates longer uninterrupted duration in the field. A horn speaker kit is available to provide voice or audio challenge. OCULi HD can be telephoned to make a two-way voice call.

The PIR detection range is 15m x 90° using a quad sensor which matches the camera's field of view. A switchable IR-cut filter means you will see realistic colour images by day and still be able to see images in the dark by way of the powerful built in IR illumination. The PIR settings are adjustable within the web portal, allowing the user to configure sensitivity, and/or gating and pulse counting, as well as the day/ night threshold. OCULi HD is fully tamper protected with IR anti-masking, 3 axis inertia sensing and enclosure tampers.


OCULI HD becomes a complete security solution when combined with webeyeCMS which enables alarm notifications and video to be sent to your own mobile device or browser (no expensive hardware or infastructure required). The all-in-one unit, when bought from Webeye, comes pre-configured so works out of the box.

Example Scenario




Dimensions

190mm



146.5mm



Basic Information

Power Requirements	2 x 3.6 lithium D cells OR 2 x 3.7v rechargable Li-ion (not included, ask	
	sales)	
Mobile Data	4G to dedicated cloud server	
Battery Life	6-9 months on 3.6v lithium D cells at 2MB	
SIM Card	Single and multi network SIMs available	
Weight	850g (without batteries)	
Operating Temprature Range	-20°C to +60°C	
Mounting Height	2.4 to 4 meters	
Weather Rating	IP66	
Warranty	2 Years	

Detector Information

Motion Detector Type	Passive Infrared
Sensor Type	2 Dual Pyro's
Lens Type	Fresnel
Detection Range	15m x 90° HOV

Transmitted Events

Tamper	Signal Strength
Anti-Masking	Heart Beat

Camera Information

Selectable Camera	640 x 480
Resolution	1280x720
	1920x1080
	2560x1944
Camera Lens	70° Horizontal
Video Sequence	2 frames per second over 7 seconds
	(5 frames per second max)

Lighting Information

IR LED	IR Frequency 850nm
IR Power	1A / 2.5W
IR Distance	10 Meters

Δ	\mathbf{c}	es:	20	96
\			~ \ U	

Accessories		
	Part Code	
Solar Kit	OCULISOLARKIT	
Horn Spraker	OCULIHORNSPEAKER	